

IN THE CLAIMS

Please amend the claims as follows:

Claims 1-16 (Canceled).

Claim 17 (Currently Amended): A sliding door, comprising:

a cam guide;

at least one shutter;

a clamp configured to be fixed to said at least one shutter;

a pair of first carriages; and

a pair of second carriages, said second carriages being supported and guided by a rail, which ~~is realized by~~ includes a profile, wherein the profile ~~is placed~~ extends along a length of an opening which is to be opened and closed by said sliding door, ~~for translating and~~ said second carriages translate along said opening along the profile;

wherein said clamp is configured to link said at least one shutter to said pair of first carriages,

each one of said first carriages is translatable longitudinally along a respective one of said second carriages and is translatable ~~relatively~~ relative to the other of said first carriages, and

said cam guide comprises grooves into each of which a roller of said first carriages respectively ~~can engage~~ engages such that each roller is movable longitudinally and ~~coaxially~~ transversely with respect to said rail.

Claim 18 (Currently Amended): The [[A]] sliding door according to claim 17, wherein for longitudinal translation of the first carriages along tracks of their respective

longitudinal second carriages, said shutter is translatable transversally with respect to the axis of the rail, which is orientated longitudinally to the opening to be closed and opened.

Claim 19 (Currently Amended): The [[A]] sliding door according to claim 17, wherein said at least one shutter is linked to the pair of first carriages by one or more clamps, which cause the at least one shutter to ~~for accomplishing movement resulting from move as a~~ result of movement of the longitudinal translation of the second carriages along the rail ~~matched and~~ with the transversal movement of the first carriages as an effect of their respective engagement with the grooves.

Claim 20 (Currently Amended): The [[A]] sliding door according to claim 19, wherein each one of said first carriages includes guide rollers, ~~or another sliding system, for being translatable~~ configured to translate along the tracks of said second carriages which respectively include a pulley for sliding along the rail for support and the translation of the at least one shutter.

Claim 21 (Currently Amended): The [[A]] sliding door according to claim 20, wherein one of said first carriages is ~~placed~~ located laterally [[to]] of said at least one shutter, ~~so that and~~ its guide roller ~~can be~~ is housed and ~~can slide~~ slides to [[bent]] curved ends of a long groove of said grooves of the guide cam.

Claim 22 (Currently Amended): The [[A]] sliding door according to claim 20, wherein one of said first carriages is placed on the center line of a longitudinal side of the at least one shutter, ~~so that and~~ its guide roller ~~can be~~ is housed and ~~can slide~~ slides to [[bent]] curved ends of a short groove portion of said grooves of the guide cam.

Claim 23 (Currently Amended): The [[A]] sliding door according to claim 17, wherein one of said first carriages is placed ~~respectively~~ on an outer edge and another of the first carriages is placed ~~the other one on the~~ a center line of an upper side of the at least one shutter, said first carriages being steadily linked to the at least one shutter by one or more ~~elamps.~~

Claim 24 (Currently Amended): The [[A]] sliding door according to claim 17, wherein one of said first carriages is ~~placed~~ disposed on the outer edge and the other [[one]] of the first carriages is disposed ~~on the~~ a center line of a lower side of the at least one shutter ~~by one or more elamps.~~

Claim 25 (Currently Amended): The [[A]] sliding door according to claim 19, wherein said second carriages each further ~~comprising~~ include a pulley and a sliding wheel that is slidable on a track of the profile, the profile including a shoulder ~~for acting that acts~~ together with the support and guide of the ~~at least one shutter~~ pair of second carriages during the translation along the rail.

Claim 26 (Currently Amended): The [[A]] sliding door according to claim 20, wherein the pulley of the second carriages further ~~comprising~~ includes a flaring member.

Claim 27 (Currently Amended): The sliding ~~Sliding~~ door according to claim 20, wherein one of the second carriages further comprises a [[stop]] loose wheel ~~acting as~~ engaging a shoulder on the track, ~~to assure linearity of the translation of the at least one shutter.~~

Claim 28 (Currently Amended): The [[A]] sliding door according to claim 17, further comprising a device configured ~~for leading and controlling~~ to lead and control opening of the at least one shutter so as to be opened or to be closed ~~for the respective overlapping and coplanarity~~, said guide device being positioned on a side opposite a longitudinal side of said at least one shutter, said guide device being configured ~~for a distribution of~~ to distribute stress in a position of inclination or partial hinging of said at least one shutter upon moving of said at least one shutter.

Claim 29 (Currently Amended): The [[A]] sliding door according to claim 28, wherein said device configured to lead and control opening of the at least one shutter further ~~comprising~~ comprises a transmission shaft ~~which is~~ linked to a section of the profile and configured to ~~for the~~ support [[of]] the second carriages, ~~by interposition of~~ via a roller that slides on the sides of an opening of the section, said shaft being ~~steadily~~ fixed to the shutter by supports, and an opposite extremity of the shaft being adjustable to slide inside an opening of a guide ~~which is~~ placed on a side opposite ~~where~~ the carriages ~~and little-carriage system are located~~.

Claim 30 (Currently Amended): The [[A]] sliding door according to claim 28, further comprising a transmission shaft which has an upper extremity ~~thereof~~ engaged in the opening of the profile, ~~the first carriage having an upper pulley,~~ a pulley of the second carriage and the roller of the first carriage being linked to a ceiling portion of the opening, and an opposite extremity of the shaft being engaged in a linear guide placed on a bottom portion of the opening.

Claim 31 (Currently Amended): The [[A]] sliding door according to claim 30, wherein the linear guide further ~~comprising~~ includes a guide cam ~~which is~~ identical in shape with and [[is]] positioned parallel to the guide cam of a ceiling portion of the opening, and including a lower pivot for sliding of the at least one shutter ~~without use of the shaft~~.

Claim 32 (Currently Amended): The [[A]] sliding door according to claim 24, ~~further comprising a~~ wherein the guide cam ~~which is~~ provided in a ceiling portion of the opening and wherein the at least one shutter to be guided and controlled by the first carriages with the second carriages is supported by ~~clamps placed~~ a support disposed on a lower side of the at least one shutter.

Claim 33 (Currently Amended): A sliding door, comprising:  
a cam guide;  
at least one shutter;  
a clamp configured to be fixed to said at least one shutter;  
a pair of first carriages; and  
a pair of second carriages, said second carriages being supported and guided by a rail, which is ~~realized by~~ includes a profile, wherein the profile ~~is placed~~ extends along a length of an opening which is to be opened and closed by said sliding door, ~~for translating and~~ said second carriages translate along said opening along the profile;

wherein said clamp is configured to link said at least one shutter to said pair of first carriages,

each one of said first carriages is translatable longitudinally along a respective one of said second carriages and is translatable relatively to the other of said first carriages, and

said cam guide comprises grooves into each of which a roller of said first carriages respectively ~~can engage~~ engages such that each roller is movable longitudinally and ~~coaxially~~ transversely with respect to said rail, and

wherein said grooves of said cam guide have bent ends.

Claim 34 (Currently Amended): A sliding door, comprising:

a cam guide;

at least one shutter;

a clamp configured to be fixed to said at least one shutter;

a pair of first carriages; and

a pair of second carriages, said second carriages being supported and guided by a rail, which is ~~realized by~~ includes a profile, wherein the profile is ~~placed~~ extends along a length of an opening which opening is to be opened and closed by said sliding door, ~~for translating and~~ said second carriages translate along said opening along the profile;

wherein said clamp is configured to link said at least one shutter to said pair of first carriages,

each one of said first carriages is translatable longitudinally along a respective one of said second carriages and is translatable relatively to the other of said first carriages, and

said cam guide comprises grooves into each of which a roller of said first carriages respectively can engage such that each roller is movable longitudinally and ~~coaxially~~ transversely with respect to said rail;

a guide device ~~configured for leading a control of a wide opening of the at least one shutter to be opened or to be closed for the respective overlapping and coplanarity, said guide device being~~ positioned on a side opposite of a longitudinal side of said at least one shutter, said ~~opposite~~ guide device being configured to support ~~for distribution of stress and a position~~

~~of inclination or partial hinging upon moving~~ at least one shutter upon occurrence of a different position of the first carriage during translation thereof into the respective bent portions of the guide cam;

a transmission shaft ~~which is~~ linked to a section of the profile and that supports for the support of the second carriages, ~~by interposition of~~ via a roller that slides on the sides of an opening of the section, said shaft being fixed to the shutter by supports, and wherein an opposite extremity of the shaft is adjustable to slide inside an opening of a guide ~~which is~~ placed on a side opposite ~~where the~~ first and second carriages ~~and little carriage system are located;~~

wherein the transmission shaft has an upper extremity ~~thereof~~ engaged in the opening of the profile, the upper pulley and the roller of the first carriage being linked to a ceiling portion of the opening, the opposite extremity of the shaft being engaged in a linear guide ~~placed~~ disposed on a bottom portion of the opening;

the linear guide comprising a guide cam ~~which is~~ identical in shape with and ~~and~~ [[is]] positioned ~~and~~ [[and]] parallel to the guide cam of the ceiling portion of the opening, and including a lower pivot for ~~the~~ [[the]] sliding ~~of~~ [[of]] the at least one shutter without use of the shaft; and including a guide provided in a ceiling portion of the opening and wherein the at least one shutter to be guided and controlled by the first carriages with the second carriages is supported by clamps ~~a support~~ placed on a lower side of the at least one shutter.